

JSO-1115-03-L

JSO-0515-01

JSO-1615-03-L

JSO SERIES

JACK SCREW STANDOFF

SPECIFICATIONS

Material:
Stainless Steel
Locking Compound:
Nylon

BOARD STACKER	A	B	BOARD STACK HEIGHT
-0415	(4.15) .163	(2.50) .098	4 mm
-0515	(5.15) .203	(3.50) .138	5 mm
-0715	(7.15) .281	(5.50) .217	7 mm
-0815	(8.15) .321	(6.50) .256	8 mm
-1015	(10.15) .400	(8.50) .335	10 mm
-1115	(11.15) .439	(9.50) .374	11 mm
-1615	(16.15) .636	(14.50) .571	16 mm

ALSO AVAILABLE (MOQ Required)

- Other heights
- Locking compound removed

Notes:
Patent Pending

Standoffs are designed,
0.15 mm longer than
connector stack heights to
allow for processing variables.

Some sizes, styles and
options are non-standard,
non-returnable.

JSO

BOARD
STACKER

LEAD STYLE

LOCKING OPTION



Specify
BOARD STACKER
from chart

-01
= Press-In
(-0415, -0515, -0715, -0815 only)


-03
= Male Thread
(-0815, -1015, -1115, -1615 only)

-L

= Locking compound
(Not available with -01 lead style,
Required for -03 lead style)




-01 LEAD STYLE




-03 LEAD STYLE

Components are to be packaged in separate bags unassembled.


APPLICATION




1




2



3



4



5

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.TOBY.CO.UK

All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.