

MODULAR JACKS AND PLUGS: GLX Series
Right Angle Modular Jack

Product Features

- 0.570" Height
- Snap-In Board Retention Tabs
- Available in 4, 6, 8 and 10 Position Housings
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

Performance Specifications

Materials and Finish

- Housing Material**
PBT Thermoplastic, UL 94V-0 Rated
- Contact Material**
Phosphor Bronze

Electrical Characteristics


- Insulation Resistance**
500 Megohms Min.
- Dielectric Withstanding Voltage**
1000V RMS, 60Hz
- Contact Resistance**
20 milliohms Max.
- Current Rating**
1.5A
- Voltage Rating**
125V DC



Generated Part Number

GLX-N-66

Part Number Builder



Series

GLX - Right Angle Modular Jack

Shield Options

- A - Non-Shielded with Panel Stops
- N - Non-Shielded without Panel Stops

Number of Positions / Contacts

- 44 - 4 Positions / 4 Contacts
- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts

Other Option

Plating Option

- Blank - Gold Flash
- 50 - 50µ" Gold Plating

Color Option

- Blank - Gray
- BLK - Black

GLX Series

Dimensions in mm

GLX-A-44xx

