



BSW-110-24-T-S

BSW-124-04-T-S-S

BSW-115-04-G-D

BSW SERIES

(2.54 mm) .100"

BOTTOM MOUNT SOCKET STRIPS

Mates with:

TSW, MTSW, HTSW,
MTLW, TSM, EW, ZW,
HW, DW, PHT

FEATURES

- Bottom mount socket strips accept .025" SQ terminals.
- Ideal for soldering and plugging from the same side of the board.
- For low-profile connections and high temperature soldering.

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?BSW

Insulator Material:

Black Thermoplastic

Insulation Resistance:

5000 MΩ min

Contact Material:

Phosphor Bronze

Plating:

Au or Sn over

50 μ" (1.27 μm) Ni

Operating Temp Range:

-55 °C to +125 °C with Gold

-55 °C to +105 °C with Tin

Withstanding Voltage:

1000 VRMS @ 60 Hz

Insertion Depth:

(3.68 mm) .145" to

(6.35 mm) .250"

RoHS Compliant:

Yes

Lead-Free Solderable:

Wave only

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- Other platings
- Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.

BSW	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION									
<p>02 thru 36</p>			<p>-04 = Standard Lead</p> <p>-24 = Low Insertion Force</p>	<p>-L = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail</p> <p>-G = 20 μ" (0.51 μm) Gold contact, Gold Flash on tail</p> <p>-T = Matte Tin (N/A with Low Insertion Force)</p>	<p>-S = Standoffs for single and double rows only.</p> <p>(-S & -D only)</p>										
<table border="1"> <thead> <tr> <th>Row Option</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>-S*</td> <td>(4.31) .170</td> </tr> <tr> <td>-M</td> <td>(3.43) .135</td> </tr> <tr> <td>-E</td> <td>(2.54) .100</td> </tr> <tr> <td>-D*</td> <td>(4.32) .170</td> </tr> </tbody> </table> <p>*Less (0.38 mm) .015" with standoffs</p>		Row Option	Z	-S*	(4.31) .170	-M	(3.43) .135	-E	(2.54) .100	-D*	(4.32) .170				
Row Option	Z														
-S*	(4.31) .170														
-M	(3.43) .135														
-E	(2.54) .100														
-D*	(4.32) .170														

Row Option	X	Y
-S	(2.54) .100	(5.08) .200
-M	(3.81) .150	(6.35) .250
-E	(4.31) .170	(6.86) .270

Body design may vary slightly from drawing shown.

- S** = Single Row
- M** = Single Row More Plug Space
- E** = Single Row Extended Plug Space
- D** = Double Row

APPLICATIONS

Due to technical progress, all designs, specifications and components are subject to change without notice.