

Specification of Anti-Static Tape

Part- VAST-xx



Non Static Generating Adhesive Tape.

VAST-12: 12mm wide

VAST-18: 18mm wide

VAST-25: 25mm wide

216 ft in length.

Manufactured from a natural fibre base, film coated with rubber based adhesive.

The tape is transparent light blue and so will not obscure printed messages or instructions. The rolls are individually wrapped to protect them from contamination, which might subsequently damage the item to which the tape is applied.

Technical Data

Thickness of Tape μ	45
Tensile Strength (N/25mm)	90
Elongation at Break (%)	18
Peel Adhesion (N/25mm)	8.5
Surface Resistivity 23°C 50%RH (ohms/sq.mm)	10_{10}
Static Charge Retention (using Princeton Static Charge Analyser)	Immediate Decay

Application

Tape is suitable for sealing conductive plastic bags used for the protection of electrostatic sensitive devices.

Tape can be written on with a spirit-based marker, which removes easily and cleanly without leaving adhesive deposits. These properties also make the product suitable for the temporary labelling of ESSD's, for eg. as might be required during inspection and quality control procedures.

The information contained within this spec sheet is for guidance only. We make no warranties expressed or implied and assume no liability regarding any use of this information.

(Re-view July 15)