

# A23b DIN 41612 IDC TYPE FEMALE TRIPLE ROW (A+C)

**PITCH: 2.54mm \* 2.54mm**


## SPECIFICATIONS

### Material


Insulator : PBT, glass reinforced, rated UL 94V-0  
 Contact : Phosphor Bronze

### Electrical

Current Rating : 1 Amp  
 Contact Resistance : 30 mΩ max.  
 Insulation Resistance : 3000 MΩ min.  
 Dielectric Withstanding Voltage : 500V AC for 1minute  
 Operating Temperature : -40°C to +105°C  
 ▶ Terminated with L01-1.27mm pitch flat ribbon cable.  
 ▶ Mating Suggestion : A23d series.



POSITION	A	B	C	D
32(A+C)	55	50	38.10	44.4
64(A+C)	95	90	78.74	85.0



**How to order:** A23b - 1 - 2 - 3 - 4 - 5 - G(RoHS)

1.NO. OF CONTACT	2.CONTACT TYPE	3.CONTACT MATERIAL	4.CONTACT PLATING	5.INSULATOR COLOR
32 64	F: FEMALE	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	2. GREY