REVISION NOTES: 1. CUSTOM JSOM FOR VITA MEZZANINE APPLICATIONS. 3/21/2017 ECN-297253 2. CX-X-XX REPRESENTS A CRITICAL DIMENSION. ISSUE FOR REVIEW. 3. STANDOFFS TO BE USED WITH 1.50[.059]MIN THICK BOARDS. JW 4. STANDOFFS ARE DESIGNED 0.15MM LONGER THAN CONNECTOR 4/24/2017 ECN-PENDING STACK HEIGHTS TO ALLOW FOR PROCESSING VARIABLES. ADD CALLOUT VIEW; EXPLODED 5. TORQUE TO 2.5 – 3.5 IN*LBS TO SECURE FASTENER IN A STATIC ENVIRONMENT VIEW: CHG DIA 6.00 TO DIA 5.80, CH 8.00 TO "A"; TOP VIEW: CHG 8.50 TO ASSUMING RECOMMENDED BOARD TO BOARD DISTANCES ARE ACHIEVED B"; BOM: CHG ASP-198473-01-B TO WITHOUT DAMAGE TO THE PCB, HARDWARE OR OTHER COMPONENTS. ASP-198473-XX-B (SEE TABLE 1). 6. COMPONENTS TO BE BULK PACKAGED IN SEPARATE BAGS AND SHOULD CHG ASP-198475-01-C TO ASP-198475-XX-C (SEE TABLE 1); ADD NOT LIST INDIVIDUAL COMPONENT QUANTITY ON THE LABEL. ALL COMPONENT TABLE 1: NOTE 1: CHG "M2.5..." TO BAGS ARE TO BE PACKAGED IN A LARGER BAG WITH THE FINAL PART NUMBER CUSTOM ...": TITLE BLOCK. QUANTITY OF ASSEMBLIES ON THE LABEL. DESCRIPTION: CHG MODIFIED TO 4.90[.193] 1.88[.074] HEX REF REF **NOT RELEASED** FOR PRODUCTION USE FOR QUOTING, PRELIMINARY DESIGN, PROTOTYPING AND INFORMATIONAL PURPOSES ONLY 3.70 .146 BY SIGNING THIS DOCUMENT YOU ARE ACCEPTING THE CONDITIONS SET WITHIN. YOUR REQUIREMENTS MUST BE LISTED WITHIN THIS DRAWING. WHERE NO DIRECTION FROM THI CUSTOMER IS IDENTIFIED SAMTEC'S PROCESS REQUIREMENTS WILL BE USED. REF 8.70[.343] REF Ø 5.80[.228] REF П C1-B-DC "À' REF 4.76 .188 REF ITEM NO. PART NUMBER QUANTITY MATERIAL ASP-198474-01-C 1.0000 303 STAINLESS STEEL ASP-198472-01-B 1.0000 303 STAINLESS STEEL 3 ASP-198473-XX-B (SEE TABLE 1) 1.0000 303 STAINLESS STEEL

ASP-198475-XX-C (SEE TABLE 1)

1.0000

303 STAINLESS STEEL

DESIGNED & DIMENSIONED IN MILLIMETERS[INCHES]

ASP-198471-XX

BOARD STACK HEIGHT

-01: 8.500 (WITH THREAD LOCKING SCREW)

-02: 10.000 (WITH THREAD LOCKING SCREW)

-03: 12.000 (WITH THREAD LOCKING SCREW)

-04: 8.500 (WITHOUT THREAD LOCKING SCREW)


-05: 10.000 (WITHOUT THREAD LOCKING SCREW

-06: 12.000 (WITHOUT THREAD LOCKING SCREW)

TABLE 1 "B" LEAD STYLE ASP-198473-XX-B ASP-198475-XX-C "A" ASP-198473-01-B ASP-198475-01-C 1 8.00 8.50 -01 -02 ASP-198473-02-B ASP-198475-01-C 9.50 10.00 -03 ASP-198473-03-B ASP-198475-01-C 11.50 12.00 -04 ASP-198473-01-B ASP-198475-02-C 8.00 8.50 -05 ASP-198473-02-B ASP-198475-02-C 9.50 10.00 -06 ASP-198473-03-B ASP-198475-02-C 11.50 | 12.00



THE VITAL COMPONENT



JNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: **DECIMALS** ANGLES X.X: ±0.3 [.01] X.XX: ±0.13 [.005]

X.XXX: ±0.051 [.0020]

HIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING REPRODUCTION USE PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC INC

PROPRIETARY NOTE

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com

DO NOT SCALE DRAWING SHEET SCALE: 4:1

"B"±0.05[.002]

M2.5 MICRO JACK SCREW STAND-OFF

ASP-198471-XX

3/17/2017 SHEET 1 OF 1 **RY- JESSIE W**

F:\dwa\sw\asp\198000\ASP-198471-XX.slddry