

VALCON STANDARD WIRE ASSEMBLY: HOW TO ORDER

Series (Denotes Wire UL Type)

No. Positions

End Option*

Over All Length in MM

AWG

Wire Colour**

WH396
(Pitch 3.96MM, UL1007 -22AWG -24AWG)

02 thru 16 pos
CO = Crimp Contact Only

DE = Dual end
(Same series & pos each end only*)

XXX

See Series for compatible AWG

BL = Blue
BLK = Black
BR = Brown
GR = Grey
G = Green
GY = Green/Yellow
O = Orange
P = Pink
R = Red
V = Violet
W=White
Y = Yellow

XH250
(Pitch 2.50mm UL1007 -22AWG -24AWG -26AWG -28AWG)

02 thru 12 pos
CO = Crimp Contact Only

SE = Single End
(To Butt Cut end Only*)

DE option = min 50mm O.A.L.
SE option = min 35mm O.A.L.

0800
(Pitch 1.25mm UL1061 -28AWG)

02 thru 15 pos
CO = Crimp Contact Only

* Other end options available.
Contact Toby for details on Toby **TCP** Series

Tolerance to +/-5mm

AM254
(Pitch 2.54mm UL1061 -24AWG -26AWG -28AWG)

02 thru 20 pos
CO = Crimp Contact Only

1800
(Pitch 2.54mm UL1007 -22AWG -24AWG -26AWG -28AWG)

01 thru 16 pos
CO = Crimp Contact Only

PH200
(Pitch 2.00mm UL1007 -26AWG -28AWG)

02 thru 16 pos
CO = Crimp Contact Only

3025
(Pitch 3.00mm UL1007 -26AWG -28AWG)

02 thru 24 pos
(Increments 2 pos)
CO = Crimp Contact Only

3020
(Pitch 3.00mm UL1007 -26AWG -28AWG)

02 thru 24 pos
(Increments 2 pos)
CO = Crimp Contact Only

5700
(4.20mm UL1007 - 18AWG -20AWG -22AWG)

02 thru 24 pos
(Increments 2 pos)
CO = Crimp Contact Only

TCP
Custom Assembly. Contact Toby for your requirements

** Multiple Wire Colour options available. Contact Toby for details on Toby **TCP** Series

Pull Out Force Test Standard - EN 60352-2

AWG	Conductor Cross Section mm ²	Tensile Strength of Conductor		Pull Force	
		N	kg	kg	N
32	0,032	8	0,81	0,4079	4
30	0,051	12	1,22	0,6118	6
28	0,081	18	1,83	1,1217	11
26	0,129	29	2,95	1,5296	15
		32	3,26	1,8355	18
24	0,205	47	4,80	2,8552	28
		57	5,80	3,2631	32
22	0,326	74	7,50	4,0789	40
20	0,518	117	11,90	6,1183	60
		169	17,22	8,6676	85
18	0,823	186	19,00	9,1774	90
		225	22,90	11,0129	108
16	1,309	295	30,00	13,7662	135
		338	34,40	15,2957	150
14	2,081	468	47,70	20,3943	200
		563	57,40	23,4535	230
12	3,309	745	76,00	28,0422	275
		900	91,70	31,6112	310
10	5,261	1186	120,00	36,1999	355
		1350	137,60	36,7098	360
8	8,367			37,7295	370
				38,7492	380

