





REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
V1.0	DWG.REL	2023.9.08	ZHANG	JIN




SECTION A-A

- Material
 - ØHousing : PA66, UL94V-0
 - ØPin header : Copper alloy, Tin plated
- Electrical
 - UL IEC
 - Rated voltage : 300V 320V
 - Rated current : 15A 20A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance: 500MΩ/DC500V
 - Withstanding Voltage : AC2000V/1min
- Mechanical
 - Operating temperature: -40℃~+105℃
 - Soldering temperature: 250℃±5/5sec
- Conform to REACH and RoHS

HOW TO ORDER
VTB2-EDGCV-P-500-xP-G

No. of poles: 2~24P
Color: G: Green



P.C.B. LAYOUT

Pitch range		Nominal dimension range			PROJECTION		TITLE		
>0 ~ 6	>6 ~ 10	>10 ~ 30	>30 ~ 60	>60 ~ 100	0.1/10	UNIT	VTB2-EDGCV-P-500-xP-G		
>6 ~ 10	>10 ~ 24	>30 ~ 60	>60 ~ 100	>100 ~ 150	<	mm			
					SHEET SIZE	A4	SERIES VTB2-EDGCV		
>0.15		>0.20	>0.30	>0.40	>0.50	>0.70	>1.00	>1.30	>2"
DRAWING TYPE		CUSTOMER DRAWING							
SCALE		1:1	SHEET	1 OF 1					
DRAWING NO.		W10000672							
TOBY ELECTRONICS LTD sales@toby.co.uk toby.co.uk									