



MINIATURE CIRCULAR CONNECTORS



CRIMPING TYPE



1983 - 2003
TWENTY YEARS



STANDARD TYPE
(MDC-163~MDC-168)



QUICK LOCK TYPE
(MDC-173~MDC-178)

Specifications

Rating: 100V AC 1A MAX or
12V DC 2A MAX

Insulation Resistance:
50MΩ MIN at 250V DC

Dielectric Strength:
250V AC/1 minute

Contact Resistance:
30mΩ MAX

Insertion Force:
4.5kg MAX

Withdrawal Force:
0.9kg~3kg

Wire: Awg #26

WIRE: AWG #26 (±1061)

ARRANGEMENT OF CONTACTS						
NO OF CONTACTS	3	4	5	6	7	8
MODEL NO	MDC-163	MDC-164	MDC-165	MDC-166	not available	MDC-168
MODEL NO	MDC-173	MDC-174	MDC-175	MDC-176	not available	MDC-178
WIRE COLOR	1 2 3 4 5 6 7 8	BLACK GREEN YELLOW RED -- -- -- --	BLACK GREEN YELLOW RED -- -- -- --	BROWN BLACK GREEN YELLOW RED -- -- --	BROWN WHITE BLACK GREEN YELLOW ORANGE RED --	BROWN WHITE BLACK BLUE GREEN YELLOW ORANGE RED

*** WIRE LENGTH AND COLOR CAN BE CHANGED AS PER CUSTOMER'S REQUEST.