





Electrical Specifications

Insulation Resistance:
100 megohms at 500V DC

Contact Resistance:
30 milliohms max.

Dielectric Withstanding Voltage:
500V for 1 minute

Item	Material	Finish
①	PBT+15%GF	BLACK
②	BRASS	NICKEL PLATED
③	P-BRONZE	NICKEL PLATED
④	P-BRONZE	NICKEL PLATED
⑤	PE	BLACK

Part Number	Center Post Diameter
KLDX-PA-0202-A-LT	2.10mm
KLDX-PA-0202-B-LT	2.60mm

the **vital**
component

RoHS COMPLIANT
EU Directive 2002/95/EC



Tolerances
X.X ± 0.35
X.XX ± 0.25
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	09/02/11	New Drawing	S. Vien	H. MA	S. Vien	08/30/11
A1	10/24/11	Release Drawing	H. MA	N/A		
A2	05/07/12	Remove CSA	S. Vien	C. Kelleher		
A3	01/16/13	ECO #12-063	S. Vien	P. DalCanto		

KLDX-PA-0202-x-LT

DC Power Plug, With Over Mold, RoHS Compliant

2.1mm, 2.6mm Diameter, Locking Type

