



AUDIO JACKS: STX-3500 Series
Surface Mount 3.5mm Stereo Jack

Product Features

Audio Applications for Computers and Multimedia
Surface Mount Design
All Plastic
CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, Black Color,
UL94V-0 Rated

Terminals

Copper Alloy, Silver Plating over Nickel Underplate

Mechanical Characteristics

Insertion Force

3.0kg Max.

Extraction Force

0.2kg Min.

Durability

5000 Mating Cycles

Electrical Characteristics

Contact Resistance

Before Durability Test

50 milliohms Max.

After Durability Test

100 milliohms Max.

Insulation Resistance

100 Megohms Min. at 500V DC

Dielectric Withstanding Voltage

500V AC RMS for 1 Minute

Operating Temperature

-25°C to + 85°C



Generated Part Number

STX-3500-3NTR

Part Number Builder

STX-3500	-	3	N	TR
Series		Number of Pins	Threading Option	Packaging Option

Series

STX-3500 - Surface Mount 3.5 Audio Jack

Number of Pins

- 3 - Pins
- 4 - Pins
- 5 - Pins

Threading Option

N - Non-Threaded Barrel

Packaging

TR - Tape and Reel

STX-3500 Series

Dimensions in mm

STX-3500-5N

