



(2.00 mm) .0787"

STMM, ZSTMM SERIES

SHROUDED IDC HEADER & STACKER

Mates with:
TCSD (except -SR)

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?STMM or www.samtec.com?ZSTMM

Insulator Material:
High Temperature Nylon

Terminal Material:
Phosphor Bronze

Plating:
Sn or Au over
50µ" (1.27 µm) Ni

Operating Temp Range:
-55°C to +105°C with Tin;
-55°C to +125°C with Gold

RoHS Compliant:
Yes

Processing:
Lead-Free Solderable:
Yes

SMT Lead Coplanarity:
(0.10 mm) .004" max

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



STMM	1	NO. PINS PER ROW	02	PLATING OPTION	D	TAIL OPTION	OTHER OPTION
<p>04, 05, 06, 07, 08, 10, 12, 13, 14, 15, 17, 20, 22, 25 (Standard sizes)</p>			<p>-F = Gold flash on post, Matte Tin on tail</p> <p>-L = 10µ" (0.25 µm) Gold on post, Matte Tin on tail</p> <p>-T = Matte Tin</p>		<p>Leave blank for Through-hole</p> <p>-RA = Right Angle</p> <p>-SM = Surface Mount</p>		<p>-“XX” = Polarized Position</p> <p>-LC = Locking Clip (-SM only) (Manual placement required)</p> <p>-K = (7.50 mm) .295" DIA Film Pick & Place Pad (-SM only)</p> <p>-TR = Tape & Reel (-SM only)</p>

ALSO AVAILABLE (MOQ Required)

- Other sizes
 - Other platings
- Contact Samtec.

OTHER SOLUTIONS

- Shrouded board-to-board headers and stackers to mate with SQT, SQW, ESQ and SMM Series. See LTMM and ZLTMM Series.

Note: For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact ipg@samtec.com for more information.

Note: This Series is non-standard, non-returnable.

ZSTMM	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	D	BODY HEIGHT	OTHER OPTION																																				
<p>04, 05, 06, 07, 08, 10, 12, 13, 14, 15, 17, 20, 22, 25 (Standard sizes)</p>			<p>Specify LEAD STYLE from chart.</p>	<p>-F = Gold flash on post, Matte Tin on tail</p> <p>-L = 10µ" (0.25 µm) Gold on post, Matte Tin on tail</p> <p>-T = Matte Tin</p>		<p>-“XXX” = Body Height</p> <p>-“XX” = Polarized Position</p>																																					
			<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>B (OAL)</th> <th>MAX BODY HEIGHT</th> </tr> </thead> <tbody> <tr><td>-75</td><td>(9.58) 0.377</td><td>(7.42) 0.292</td></tr> <tr><td>-62</td><td>(10.08) 0.397</td><td>(7.92) 0.312</td></tr> <tr><td>-65</td><td>(10.49) 0.413</td><td>(8.33) 0.328</td></tr> <tr><td>-73</td><td>(12.09) 0.476</td><td>(9.93) 0.391</td></tr> <tr><td>-63</td><td>(14.10) 0.555</td><td>(11.94) 0.470</td></tr> <tr><td>-66</td><td>(15.09) 0.594</td><td>(12.93) 0.509</td></tr> <tr><td>-69</td><td>(15.60) 0.614</td><td>(13.44) 0.529</td></tr> <tr><td>-74</td><td>(17.09) 0.673</td><td>(14.94) 0.588</td></tr> <tr><td>-70</td><td>(17.60) 0.693</td><td>(15.44) 0.608</td></tr> <tr><td>-71</td><td>(21.08) 0.830</td><td>(18.92) 0.745</td></tr> <tr><td>-72</td><td>(21.62) 0.851</td><td>(19.46) 0.766</td></tr> </tbody> </table>					LEAD STYLE	B (OAL)	MAX BODY HEIGHT	-75	(9.58) 0.377	(7.42) 0.292	-62	(10.08) 0.397	(7.92) 0.312	-65	(10.49) 0.413	(8.33) 0.328	-73	(12.09) 0.476	(9.93) 0.391	-63	(14.10) 0.555	(11.94) 0.470	-66	(15.09) 0.594	(12.93) 0.509	-69	(15.60) 0.614	(13.44) 0.529	-74	(17.09) 0.673	(14.94) 0.588	-70	(17.60) 0.693	(15.44) 0.608	-71	(21.08) 0.830	(18.92) 0.745	-72	(21.62) 0.851	(19.46) 0.766
LEAD STYLE	B (OAL)	MAX BODY HEIGHT																																									
-75	(9.58) 0.377	(7.42) 0.292																																									
-62	(10.08) 0.397	(7.92) 0.312																																									
-65	(10.49) 0.413	(8.33) 0.328																																									
-73	(12.09) 0.476	(9.93) 0.391																																									
-63	(14.10) 0.555	(11.94) 0.470																																									
-66	(15.09) 0.594	(12.93) 0.509																																									
-69	(15.60) 0.614	(13.44) 0.529																																									
-74	(17.09) 0.673	(14.94) 0.588																																									
-70	(17.60) 0.693	(15.44) 0.608																																									
-71	(21.08) 0.830	(18.92) 0.745																																									
-72	(21.62) 0.851	(19.46) 0.766																																									